Certificate Number UL-CA-2202432-1

Report Reference E521307-20211229

Date 7-Sep-2022

Issued to: Atomic Tiger Ltd

Room 03, 7th FI, Tamson Plaza

161 Wai Yip St Kwun Tong Kowloon

Hong Kong

This is to certify that representative samples of

IFDR7 - Low-voltage Lighting Systems, Power Units,

Luminaires and Fittings Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: CSA C22.2 NO. 250.2, 1st Ed., Issue Date: 2020-01-01

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.






Bruce Mahrenholz, Director North American Certification Program

Certificate Number UL-CA-2202432-1
Report Reference E521307-20211229

Date 7-Sep-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
FMB06CDDEF-GGHIJJ, Series name: FMB = Flush Mount LED Bolt Thread Diameter, which may be "06" = 6 mm Brightness, which may be Blank = normal brightness Bezel Structure, which may be Blank = Without Secure Cap Protection on Top, which may be Blank = Without Lens. Body, which may be Blank = Normal Length Housing Material, which may be "AL" = Aluminum LED Color (CH1), which may be "W" = White, "R" = Red,	Low Voltage Lighting Systems
"G" = Green, "B" = Blue, "A" = Amber, "P" = Purple LED Color (CH2), which may be Blank for commercial use Main Function, which may be Blank = No Special	
Function	$<$ \times \times \times \times
FMB11CDDEF-GGHIJJ, Series name: FMB = Flush Mount LED Bolt	Low Voltage Lighting Systems
Thread Diameter, which may be "11" = 11 mm Brightness, which may be "H" = High, "L" = Low Bezel Structure, which may be "SC" = with Secure Cap or Blank = Without Secure Cap Protection on Top, which may be "D" = Dome Lens, "F" = Flat Lens or Blank = Without Lens. Body, which may be "S" = Shorter Version or Blank =	
Normal Length Housing Material, which may be "AL" = Aluminum, "SS" = Stainless Steel or "BS" = Brass LED Color (CH1), which may be "W" = White, "R" = Red,	
"G" = Green, "B" = Blue, "A" = Amber, "P" = Purple LED Color (CH2), which may be "W" = White, "R" = Red, "G" = Green, "B" = Blue, "A" = Amber, "P" = Purple or	
Blank for commercial use	
Main Function, which may be "CR" = Constant Regulator, "SB" = Switch Back, "DB" = Dual Brightness or Blank = for commercial use	
FMB16CDDEF-GGHIJJ, Series name: FMB = Flush Mount LED Bolt Thread Diameter, "16" = 16 mm Brightness, which may be "H" = High, "L" = Low	Low Voltage Lighting Systems






Certificate Number UL-CA-2202432-1
Report Reference E521307-20211229

Date 7-Sep-2022

Bezel Structure, which may be "SC" = with Secure Cap or Blank = Without Secure Cap
Protection on Top, which may be "D" = Dome Lens, "F" = Flat Lens or Blank = Without Lens.
Body, which may be Blank = Normal Length
Housing Material, which may be "AL" = Aluminum, "SS"
= Stainless Steel or "BS" = Brass
LED Color (CH1), which may be "W" = White, "R" = Red, "G" = Green, "B" = Blue, "A" = Amber, "P" = Purple
LED Color (CH2), which may be "W" = White, "R" = Red, "G" = Green, "B" = Blue, "A" = Amber, "P" = Purple or Blank for commercial use
Main Function, which may be "CR" = Constant
Regulator, "SB" = Switch Back, "DB" = Dual Brightness or Blank for commercial use





 Certificate Number
 UL-US-2202430-1

 Report Reference
 E521307-20211229

Date 7-Sep-2022

Issued to: Atomic Tiger Ltd

Room 03, 7th FI, Tamson Plaza

161 Wai Yip St Kwun Tong Kowloon

Hong Kong

This is to certify that representative samples of

IFDR - Low-voltage Lighting Systems, Power Units,

Luminaires and Fittings

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 2108, 2nd Ed., Issue Date: 2015-12-7, Revision Date:

2021-12-30

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.






Certificate Number UL-US-2202430-1
Report Reference E521307-20211229

Date 7-Sep-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
FMB06CDDEF-GGHIJJ, Series name: FMB = Flush Mount LED Bolt Thread Diameter, which may be "06" = 6 mm Brightness, which may be Blank = normal brightness Bezel Structure, which may be Blank = Without Secure Cap Protection on Top, which may be Blank = Without Lens. Body, which may be Blank = Normal Length Housing Material, which may be "AL" = Aluminum LED Color (CH1), which may be "W" = White, "R" = Red, "G" = Green, "B" = Blue, "A" = Amber, "P" = Purple	Low Voltage Lighting Systems
LED Color (CH2), which may be Blank for commercial	
use	
Main Function, which may be Blank = No Special Function	
FMB11CDDEF-GGHIJJ, Series name: FMB = Flush	Low Voltage Lighting Systems
Mount LED Bolt	zon vonago zigining eyeteine
Thread Diameter, which may be "11" = 11 mm	
Brightness, which may be "H" = High, "L" = Low	
Bezel Structure, which may be "SC" = with Secure Cap	
or Blank = Without Secure Cap	
Protection on Top, which may be "D" = Dome Lens, "F" =	
Flat Lens or Blank = Without Lens.	
Body, which may be "S" = Shorter Version or Blank = Normal Length	
Housing Material, which may be "AL" = Aluminum, "SS"	
= Stainless Steel or "BS" = Brass	
LED Color (CH1), which may be "W" = White, "R" = Red,	
"G" = Green, "B" = Blue, "A" = Amber, "P" = Purple	
LED Color (CH2), which may be "W" = White, "R" = Red,	
"G" = Green, "B" = Blue, "A" = Amber, "P" = Purple or	
Blank for commercial use	
Main Function, which may be "CR" = Constant	
Regulator, "SB" = Switch Back, "DB" = Dual Brightness	
or Blank = for commercial use	
FMB16CDDEF-GGHIJJ, Series name: FMB = Flush	Low Voltage Lighting Systems
Mount LED Bolt	
Thread Diameter, "16" = 16 mm	
Brightness, which may be "H" = High, "L" = Low	





Certificate Number UL-US-2202430-1 Report Reference E521307-20211229

Date 7-Sep-2022

Bezel Structure, which may be "SC" = with Secure Cap
or Blank = Without Secure Cap
Protection on Top, which may be "D" = Dome Lens, "F" =
Flat Lens or Blank = Without Lens.
Body, which may be Blank = Normal Length
Housing Material, which may be "AL" = Aluminum, "SS"
= Stainless Steel or "BS" = Brass
LED Color (CH1), which may be "W" = White, "R" = Red,
"G" = Green, "B" = Blue, "A" = Amber, "P" = Purple
LED Color (CH2), which may be "W" = White, "R" = Red,
"G" = Green, "B" = Blue, "A" = Amber, "P" = Purple or
Blank for commercial use
Main Function, which may be "CR" = Constant
Regulator, "SB" = Switch Back, "DB" = Dual Brightness
or Blank for commercial use



Bruce Mahrenholz, Director North American Certification Program

UL LLC

